



**NOTES:**

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- \*A CONCRETE COLLAR SHALL BE CONSTRUCTED AROUND ANY RISER LOCATED IN A TRAFFIC AREA. COLLARS SHALL BE DESIGNED BY PROJECT ENGINEER.

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



**RISER & CLEANOUT DETAIL**

DRAWN BY: JAJ  
 DATE: 6/12/2012  
 SCALE: NTS  
 SHEET: 1 of 1

DRAWING NUMBER:  
**D-5-102**