



NOTES:

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- DUE TO SLIGHT DIFFERENCES IN PRINSCO'S MANUFACTURING EQUIPMENT, 18"-48" (450-1200 mm) DIAMETER PIPE HAS MINOR DIAMETRICAL DIFFERENCES BETWEEN THE WESTCOAST AND THE MIDWEST. DUE TO THESE DIFFERENCES PLEASE VERIFY DIMENSIONS BEFORE ORDERING ANY PRESS-SEAL PRODUCT.
- SEE PRESS-SEAL FOR SPECIFIC PRODUCT INFORMATION AND SELECTION.
- PRESS-SEAL ADAPTER AND PRESS-SEAL PSX: DIRECT DRIVE ARE A REGISTERED TRADEMARK OF PRESS-SEAL GASKET CORPORATION. (WWW.PRESS-SEAL.COM)
- SEE STRUCTURE CONNECTION INSTALLATION DETAIL (D-1-109) FOR PROPER BACKFILLING TECHNIQUES NEAR STRUCTURES.

PIPE SIZE in (mm)	PIPE OD in (mm)	PRESS-SEAL ADAPTER (Prinsco PN#)	PRESS-SEAL PSX DIRECT DRIVE CONNECTOR
12 (300)	14.4 (366)	GFAD12MH	18Y
15 (375)	17.6 (447)	GFAD15MH	22L
18 (450)	21.5 (546)	GFAD18MH	24S
24 (600)	28.4 (721)	GFAD24MH	32L

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinsco.com

TITLE: HDPE PIPE - STRUCTURE CONNECTION - PRESS SEAL		REV: B
DRAWN BY: TRA	DATE: 30-Jun-17	DRAWING NUMBER: D-1-120
SCALE: NTS	SHEET: 1 OF 1	