



NOTES:

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- DUE TO SLIGHT DIFFERENCES IN PRINSCO'S MANUFACTURING EQUIPMENT, 18"-48" (450-1200 mm) DIAMETER PIPE HAS MINOR DIAMETRICAL DIFFERENCES BETWEEN THE WESTCOAST AND THE MIDWEST. DUE TO THESE DIFFERENCES PLEASE VERIFY DIMENSIONS BEFORE ORDERING ANY A-LOK PRODUCT.
- SEE Z-LOK FOR SPECIFIC PRODUCT INFORMATION AND SELECTION.
- Z-LOK IS A REGISTERED TRADEMARK OF A-LOK PRODUCTS, INC. (WWW.A-LOK.COM)
- SEE STRUCTURE CONNECTION INSTALLATION DETAIL (D-1-109) FOR PROPER BACKFILLING TECHNIQUES NEAR STRUCTURES.

PIPE SIZE in (mm)	PVC ADAPTER OD in (mm)	Z-LOK (PN#)
12 (300)	14.4 (366)	ZS-8016
15 (375)	17.6 (447)	ZS-8019
18 (450)	21.5 (546)	ZS-8022
24 (600)	28.4 (721)	ZS-8029
30 (750)	34.9 (886)	ZS-8039
36 (900)	40.8 (1036)	ZS-8045

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinsco.com

TITLE: HDPE PIPE - STRUCTURE CONNECTION -Z-LOK				REV: B
DRAWN BY: TRA	DATE: 30-Jun-17	DRAWING NUMBER: D-1-119		
SCALE: NTS	SHEET: 1 OF 1			