

# Scope

This specification designates the requirements for 6-inch Prinsco PROFORM™ HD perforated foundation form/drain lineals for use in footing forms, foundation drainage, and perimeter radon gas evacuation applications.

# **Pipe Requirements**

Prinsco PROFORM HD lineals shall have annular interior corrugations and a smooth outer shell and shall be rectangular in shape. PROFORM HD shall have 4 rows of horizontal perforations on one side of the form/drain lineals.

#### **Materials**

PROFORM HD and fittings shall be manufactured using post-consumer recycled High Density Polyethylene (HDPE) meeting the minimum requirements of cell classification 323410E as defined and described in ASTM D3350.

#### **Joint Performance**

PROFORM HD features self-coupling ends that form soil tight joints meeting the requirements of ASTM F667. PROFORM HD joints shall be assembled in accordance with the manufacturer's requirements.

# Fittings/Accessories

Fittings shall meet the material requirements of ASTM F667. Standard fittings and accessories are available as listed on Prinsco's website www.prinsco.com.

# **Physical Pipe Dimensions**

Nominal Height	Approximate Dimensions	Available Length	Corrugation Pitch	Approximate Weight/foot	Approximate Water Inlet Area/ft
(in)	(in)	(ft)	(in)	(lb)	(in²/ft)
6"	2.4 x 6.5	10	0.5	0.7	1.5



### Installation

PROFORM HD and fittings are designed to be installed level around the perimeter of a house for footing forming, subsurface drainage, and radon gas evacuation. PROFORM HD and accessories shall be installed in accordance with Prinsco's installation guidelines and the local building code. Contact your local Prinsco Representative or visit <a href="https://www.prinsco.com">www.prinsco.com</a> for the latest installation guidelines.

## **Reference Specifications**

This specification references the lasted edition and revisions of the following standard specifications:

- ASTM D3350 Standard Specifications for Polyethylene Plastics Pipe and Fittings Materials
- ASTM F667 Standard Specification for 3 through 24 in. Corrugated Polyethylene Pipe and Fittings

prinsco.com | 1717 16th St NE Willmar MN | toll free 800.992.1725 | phone 320.222.6800 | fax 320.222.6820