

Introduction

Pipe joint lubricant is generally necessary for gasketed bell and spigot joints to prevent the gasket from becoming displaced and to reduce the insertion force required to assemble the joint. Joint lubricant is especially critical for watertight applications where leakage is a concern. Prinsco has found that spray-on lubricant offers effective lubrication allowing for safe and efficient assembly of gasketed bell and spigot joints. The spray-on lubricant supplied by Prinsco does not contain petroleum, so it will not damage or swell gaskets. The spray-on lubrication allows for a consistent coverage to the bell and gasket and reduces the need for clean-up after use.

Design Features	Product Detail
<ul style="list-style-type: none"> • Easy Spray-on Application • NSF Certified for Potable Water Pipelines • Designed for Cold or Hot Weather Application • No Petroleum – Does Not Swell Gaskets • Aerosol Valve Allows for Consistent Application • Does Not Require Clean-up after Assembly 	<ul style="list-style-type: none"> • Foam Lubricant • Meets NSF Standard #61 • Does Not Contain Petroleum • Stable from 0° to 110°F • Negligible Effect on Gaskets <ul style="list-style-type: none"> ○ <1.0% Weight Gain ○ < Durometer Hardness Loss • Non Toxic • Biodegradable • Virtually Odor Free

*Do not spray near sparks, heat, or open flames. Do not smoke while using.