



NOTES:

1. A 4" (100 mm) VENT TUBE MAY BE CONNECTED THROUGH ANY CHAMBER CORRUGATION VALLEY (HS180) CHAMBER CIRCULAR CUT OUT POINT (HS75).
2. TAP TEE CONNECTION MAY CONSIST OF QWICKSEAL, INSERTA TEE OR APPROVED EQUAL.
3. ALL PVC FITTINGS TO BE SOLVENT CEMENTED.
4. PVC MAY BE EITHER SDR 35 or SCH 40.
5. PVC PIPE MAY BE SOLID OR PERFORATED PER ENGINEER.

OPTIONAL VENT DETAIL

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



**VENT TUBE DETAIL
HYDROSTOR CHAMBERS**

DRAWN BY:	BMH
DATE:	01/20/2016
SCALE:	NTS
SHEET:	1 OF 1

DRAWING NUMBER:
D-7-104