



NOTES:

1. FITTINGS ARE AVAILABLE IN TEES, WYES, REDUCERS, 45° ELBOWS AND BELL/BELL COUPLERS
2. SOIL TIGHT FITTINGS ARE SHOWN. WATERTIGHT FITTINGS ARE ALSO AVAILABLE
3. USE OF PIPE TAPE SECURES FITTINGS IN PLACE
4. CATCH BASINS TO BE PLACED IN LOW AREAS TO REMOVE SURFACE WATER

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinSCO.com

TITLE:		HDPE PIPE - INSTALLATION - ROOF & YARD CATCH BASIN		REV: B
DRAWN BY:	TRA	DATE:	03-Jul-17	DRAWING NUMBER:
SCALE:	NTS	SHEET:	1 OF 1	D-1-132