



NOTES:

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- SEE KOR-N-SEAL FOR SPECIFIC PRODUCT INFORMATION AND SELECTION.
- KOR-N-SEAL IS A REGISTERED TRADEMARK OF TRELLEBORG, INC. (WWW.TRELLEBORG.COM)
- SEE STRUCTURE CONNECTION INSTALLATION DETAIL (D-2-109) FOR PROPER BACKFILLING TECHNIQUES NEAR STRUCTURES.

PIPE SIZE in (mm)	MANHOLE ADAPTER OD in (mm)	KOR-N-SEAL (PN#)	
		SERIES 106 OR 206	SERIES 306
12 (300)	14.74 (375)	S106-20BW	NA
15 (375)	18.01 (457)	S206-22	S306-22
18 (450)	21.70 (551)	S206-26	S306-26
24 (600)	28.39 (721)	S206-32	S306-32
30 (750)	34.90 (886)	S206-38	S306-38L
36 (900)	40.84 (1,037)	S206-44	S306-44L

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinsco.com

TITLE: HP PIPE - STRUCTURE CONNECTION -		REV: C
KOR-N-SEAL WITH PIPE SLEEVE		
DRAWN BY: TSS	DATE: 16-Aug-17	DRAWING NUMBER: D-2-115
SCALE: NTS	SHEET: 1 OF 1	