



NOTES:

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- SEE KOR-N-SEAL FOR SPECIFIC PRODUCT INFORMATION AND SELECTION.
- KOR-N-SEAL IS A REGISTERED TRADEMARK OF TRELLEBORG, INC. (WWW.TRELLEBORG.COM)
- SEE STRUCTURE CONNECTION INSTALLATION DETAIL (D-2-109) FOR PROPER BACKFILLING TECHNIQUES NEAR STRUCTURES.

PIPE SIZE I.D. in (mm)	HP MANHOLE ADAPTER O.D. in (mm)	KOR-N-SEAL (PN#)	
		SERIES II 206	SERIES II 306
12 (300)	15.1(385)	S206-18L	NA
15 (375)	18.2(460)	S206-22	S306-22
18 (450)	21.9(555)	S206-26	S306-26
24 (600)	28.6(725)	S206-32	S306-32L
30 (750)	35.1(890)	S206-38L	S306-38L
36 (900)	41.3(1050)	S206-44L	S306-44L
42 (1050)	48.3(1225)	S206-52L	NA

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinsco.com

TITLE: HP PIPE - STRUCTURE CONNECTION - KOR-N-SEAL WITH PIPE SLEEVE			
DRAWN BY: NJW	DATE: 11-Aug-23	DRAWING NUMBER: D-2-115	
SCALE: NTS	SHEET: 1 OF 1		