



NOTES:

1. A 4" (100 mm) VENT TUBE MAY BE CONNECTED THROUGH A CORED HOLE, CENTERED ON A VALLEY BETWEEN (2) TWO CORRUGATIONS.
2. TAP TEE CONNECTION MAY CONSIST OF QWICKSEAL, INSERTA TEE OR APPROVED EQUAL.
3. ALL PVC FITTINGS TO BE SOLVENT CEMENTED.
4. PVC MAY BE EITHER SDR 35 or SCH 40.
5. PVC PIPE MAY BE SOLID OR PERFORATED PER ENGINEER.
6. CORE HOLE SIZE AS FOLLOWS: 4" (100 mm) CUT TO 5" (125 mm)

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinsco.com

TITLE: HYDROSTOR HS180 - VENT TUBE		REV: B
DRAWN BY: ARB	DATE: 05-Jun-17	DRAWING NUMBER: D-7-208
SCALE: NTS	SHEET: 1 OF 1	