



**NOTES:**

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- WATERTIGHT PERFORMANCE IS DEPENDENT ON INSTALLATION QUALITY.
- FOR USE ON 12"-60" PIPE.
- POLYSEAL IS A REGISTERED TRADEMARK OF MARMAC PRODUCTS INC. (WWW.MARMAC.COM)

**APPLICATION NOTES:**

- MARMAC POLYSEAL MASTIC BANDING CAN BE USED TO WRAP A SMALL DAMAGED SECTION OF PIPE, OR CAN CONNECT TWO LENGTHS OF PIPE AFTER REMOVING THE DAMAGED SECTION (SHOWN ABOVE).
- STEEL STRAPS ARE TIGHTENED AROUND PIPE TO PROVIDE A POSITIVE SEAL.
- FLOWABLE FILL AROUND COUPLER IS OPTIONAL AND NOT REQUIRED.
- REFER TO MANUFACTURER'S INSTALLATION RECOMMENDATIONS FOR FURTHER DETAIL.

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE  
WILLMAR, MN 56201  
www.prinSCO.com

TITLE: HP PIPE - PIPE REPAIR - SECTION REPLACED MARMAC			
DRAWN BY: RMA	DATE: 05-Dec-23	DRAWING NUMBER: D-2-137	
SCALE: NTS	SHEET: 1 OF 1		