



NOTES:

- ALL PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321 - STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF FLEXIBLE THERMOPLASTIC SEWER PIPE, LATEST EDITION.
- PRINSCO GOLDLINE SOILTIGHT COUPLERS ARE AVAILABLE IN SIZES FROM 12"-60" (300-1500 mm).

APPLICATION NOTES:

- SPLIT COUPLERS CAN CONNECT TWO LENGTHS OF PIPE AFTER REMOVING THE DAMAGED SECTION (AS SHOWN ABOVE).
- SPLIT COUPLERS CAN BE PLACED DIRECTLY OVER A MINIMALLY DAMAGED SECTION OF PIPE. THIS IS ONLY RECOMMENDED FOR REPAIRS IN NON-TRAFFICKED AREAS.
- SPLIT COUPLERS ARE USED TO PROVIDE A SOIL-TIGHT REPAIR OR CONNECTION.

THIS DETAIL DEPICTS RECOMMENDED INSTALLATION PRACTICES AND IS NOT INTENDED TO SUPERSEDE ANY NATIONAL, STATE OR LOCAL SPECIFICATIONS. PRINSCO BEARS NO RESPONSIBILITY FOR ANY ALTERATIONS, REVISION AND/OR DEVIATION FROM THIS STANDARD DETAIL. PRINSCO HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICE FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION TO VERIFY SUITABILITY. © PRINSCO, INC.



1717 16TH ST. NE
WILLMAR, MN 56201
www.prinsco.com

TITLE:		HP PIPE - PIPE REPAIR - SECTION REPLACED SPLIT COUPLER	
DRAWN BY:	RMA	DATE:	05-Dec-23
SCALE:	NTS	SHEET:	1 OF 1
			DRAWING NUMBER: D-2-134